

オーバースライディングドア_パネル枚数設定表 / 最大窓個数と框補強位置


開口高さH (mm)	パネル枚数	パネルピッチ			パネル 高さh	ドア高さ DH=h +水切りシール(30)	パネルのみ込み DH-H
		380	480	570			
1600~1630	3	0	1	2	1620	1650	20~50
1631~1720	"	0	0	3	1710	1740	20~109
1721~1829	4	1	3	0	1820	1850	21~129
1830~1930	"	0	4	0	1920	1950	20~120
1931~2020	"	0	3	1	2010	2040	20~109
2021~2110	"	0	2	2	2100	2130	"
2111~2200	"	0	1	3	2190	2220	"
2201~2290	"	0	0	4	2280	2310	"
2291~2410	5	0	5	0	2400	2430	20~139
2411~2500	"	0	4	1	2490	2520	20~109
2501~2590	"	0	3	2	2580	2610	"
2591~2680	"	0	2	3	2670	2700	"
2681~2770	"	0	1	4	2760	2790	"
2771~2860	"	0	0	5	2850	2880	"
2861~2890	6	0	6	0	2880	2910	20~49
2891~2980	"	0	5	1	2970	3000	20~109
2981~3070	"	0	4	2	3060	3090	"
3071~3160	"	0	3	3	3150	3180	"
3161~3250	"	0	2	4	3240	3270	"
3251~3340	"	0	1	5	3330	3360	"
3341~3430	"	0	0	6	3420	3450	"
3431~3460	7	0	6	1	3450	3480	20~49
3461~3550	"	0	5	2	3540	3570	20~109
3551~3640	"	0	4	3	3630	3660	"
3641~3730	"	0	3	4	3720	3750	"
3731~3820	"	0	2	5	3810	3840	"
3821~3910	"	0	1	6	3900	3930	"
3911~4000	"	0	0	7	3990	4020	"
4001~4030	8	0	6	2	4020	4050	20~49
4031~4120	"	0	5	3	4110	4140	20~109
4121~4210	"	0	4	4	4200	4230	"
4211~4300	"	0	3	5	4290	4320	"
4301~4390	"	0	2	6	4380	4410	"
4391~4480	"	0	1	7	4470	4500	"
4481~4570	"	0	0	8	4560	4590	"
4571~4600	9	0	6	3	4620	4050	20~49
4601~4690	"	0	5	4	4110	4140	20~109
4691~4780	"	0	4	5	4200	4230	"
4781~4870	"	0	3	6	4290	4320	"
4871~4960	"	0	2	7	4380	4410	"
4961~5000	"	0	1	8	4560	4590	"

開口高さH (mm)	パネル枚数	パネルピッチ			パネル 高さh	ドア高さ DH=h +水切りシール(30)	パネルのみ込み DH-H
		380	480	570			
5001~5050	9	0	1	8	5040	5070	20~109
5051~5140	"	0	0	9	5130	5160	"
5141~5170	10	0	6	4	5160	5190	20~109
5171~5260	"	0	5	5	5250	5280	"
5261~5350	"	0	4	6	5340	5370	"
5261~5350	"	0	3	7	5430	5460	"
5351~5440	"	0	2	8	5520	5550	"
5441~5530	"	0	1	9	5610	5640	"
5531~5620	"	0	0	10	5700	5730	"
5711~5740	11	0	6	5	5730	5760	20~109
5741~5830	"	0	5	6	5820	5850	"
5831~5920	"	0	4	7	5910	5940	"
5921~6010	"	0	3	8	6000	6030	"
6011~6100	"	0	2	9	6090	6120	"
6101~6190	"	0	1	10	6180	6210	"
6191~6280	"	0	0	11	6270	6300	"
6281~6310	12	0	6	6	6300	6330	20~109
6311~6400	"	0	5	7	6390	6420	"
6401~6490	"	0	4	8	6480	6510	"
6491~6580	"	0	3	9	6570	6600	"
6581~6670	"	0	2	10	6660	6690	"
6671~6760	"	0	1	11	6750	6780	"
6761~6850	"	0	0	12	6840	6870	"
6851~6880	13	0	6	7	6870	6900	20~109
6881~6970	"	0	5	8	6960	6990	"
6971~7060	"	0	4	9	7050	7080	"

最大窓個数と框補強位置

明かり窓・ガラリの取付は中間パネルとする。
(上パネル・鍵パネル・下パネルに明かり窓・ガラリの取付不可。)

	開口 W	窓個数	框補強位置
丸窓・ガラリ スチールタイプ用	1600~1720	1	
	1721~2920	2	
アルミ、FRPタイプ用	2921~4210	3	
	4121~5320	4	
	5321~6620	5	
	6521~7720	6	
	7721~8920	7	
	8921~10120	8	
	10121~11000	9	



縮尺

BX 文化シャッター株式会社